

# InvisiLED® OUTDOOR

Wet Rated LED Tape

# WAC LIGHTING



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

Designed for the outdoors, this durable and professional grade white tape light delivers superior color consistency and brightness throughout the strip. An IP65 Outdoor Wet Location rating, and unique silicon tube protection guards against the elements while offering 3 CCT choices to illuminate hardscaping, landscaping and architectural features.

## FEATURES

- May be cut every 4 inches
- Beam Spread: 115°
- Multiple roll lengths offered
- Equal brightness from end to end
- Protection against water spray, dust with silicone jacket (IP65)
- 100 ft max distance between the power supply and beginning of InvisiLED®

## SPECIFICATIONS

<b>Construction:</b>	Flexible strip light in silicon tube
<b>Cutting Interval:</b>	4"
<b>Input:</b>	24VDC
<b>Lumens:</b>	Up to 200 lm/ft
<b>Max Run:</b>	Refer to ordering table
<b>Dimming:</b>	ELV, TRIAC
<b>CRI:</b>	90
<b>McAdams Steps:</b>	3
<b>Color Temp:</b>	2700K / 3000K/ 4000K
<b>Rated Life</b>	50,000 hours
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL & cUL listed, Wet Location listed, Title 24 Compliant

## TAPE SELECTIONS

System		Max Run	Power	Length (in feet)						Color Temp	Finish	
<b>T24-OD1</b>	100+lm/ft	80ft	1.2W/ft	01	05	10	20	40	80	27	2700K	Black
<b>T24-OD2</b>	200+lm/ft	40ft	2.4W/ft	01	05	10	20	40	N/A	30	3000K	
										40	4000K	











Example: **T24-OD1-20-27**

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585



Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

	Model	Finish		
	T24-WE-IC-002-BK T24-WE-IC-006-BK T24-WE-IC-012-BK T24-WE-IC-036-BK T24-WE-IC-072-BK T24-WE-IC-144-BK T24-WE-IC-240-BK	Black	2 in 6 in 1 ft 3 ft 6 ft 12 ft 20 ft	InvisiLED Outdoor Joiner Cable Extends power supply lead wire
	T24-WE-BO12-BK T24-WE-BO72-BK	Black	1 ft 6 ft	InvisiLED Outdoor Lead Wire Connects to Indoor Power Supply
	T24-WE-EX2-006-BK	Black	6 in	InvisiLED Outdoor Power Connector Kit with Wire Jacket and Silicone Sealant Allows power to Wet Rated tape
	T24-WE-Y-BK	Black		InvisiLED Outdoor Tape to Tape Y Connector Splits power to the two tape sections
	T24-WE-EC	Clear		Wet Rated Tape End Cap with Silicone Sealant 24VDC Wet Rated (10 pieces)
	LED-TO24-C1	Black		InvisiLED Outdoor Surface Mounting Clip 24VDC Wet Rated Mounting Screws (10 pieces)
	LED-TO24-C2	Black		InvisiLED Outdoor Edge Mounting Clip 24VDC Wet Rated Tape Mounting Screws (10 pieces)
	T24-WE-C3	Black		InvisiLED Outdoor Underside Mounting Clip 24VDC Wet Rated Tape Mounting Screws (10 pieces)
	T24-WE-CH5	Clear	5ft	InvisiLED Outdoor Surface Mount Clear Channel
	T24-WE-SI-45	White		Silicone Sealant Wet Location Tape Sealant (45 grams)

## Power Supply

	Model	Input	Output	Dimming	
	PS-24DC-U96R-WE	120V-277VAC	24VDC 96W	ELV / TRIAC	8 3/8" x 2 13/16" x 1 11/16" ≥ 0.9 pf Overload and short circuit protection Includes 6ft lead wire
	PS-24DC-A96P-WE	120V	24V 96W	N/A	8 3/8" x 2 13/16" x 1 11/16" ≥ 0.9 pf Overload and short circuit protection Includes 6ft lead wire 120V input power cord ready